

“PALUX” Series LED Retrofit lamp

1. “PALUX” LED A60 (main voltage)

Product Code	Lamp Base	Watt	Lumen Output	Color Temperature	Ra	Beam Angle/ Lighting Spread	Average life	Certification
A60	E27/B22	6W	470 lm	3000K/4000K/6000K	≥80	130°	20000 hrs	CE/Erp
A60	E27/B22	10W	806 lm	3000K/4000K/6000K	≥80	130°	20000 hrs	CE/Erp
A60	E27/B22	13W	1055 lm	3000K/4000K/6000K	≥80	130°	20000 hrs	CE/Erp

2. “PALUX” LED G45 (main voltage)

Product Code	Lamp Base	Watt	Lumen Output	Color Temperature	Ra	Beam Angle/ Lighting Spread	Average life	Certification
G45	E14/E27	3.5W	250 lm	3000K/4000K/6000K	≥80	180°	20000 hrs	CE/Erp
G45	E14/E27	5.5W	470 lm	3000K/4000K/6000K	≥80	180°	20000 hrs	CE/Erp

3. “PALUX” LED C37 (main voltage)

Product Code	Lamp Base	Watt	Lumen Output	Color Temperature	Ra	Beam Angle/ Lighting Spread	Average life	Certification
C37	E14/E27	3.5W	250 lm	3000K/4000K/6000K	≥80	230°	20000 hrs	CE/Erp
C37	E14/E27	5.5W	470 lm	3000K/4000K/6000K	≥80	230°	20000 hrs	CE/Erp

4. “PALUX” LED Crystal G45 (main voltage)

Product Code	Lamp Base	Watt	Lumen Output	Color Temperature	Ra	Beam Angle/ Lighting Spread	Average life	Certification
G45	E27/B22/ E14/B15d	5.5W	470 lm	3000K/4000K/6000K	≥80	160°	20000hrs	CE/Rhos/Erp
G45	E27/B22/ E14/B15d	5.5W	470 lm	3000K/4000K/6000K	≥80	160°	20000hrs	CE/Rhos/Erp

5. “PALUX” LED Crystal C35 (main voltage)

Product Code	Lamp Base	Watt	Lumen Output	Color Temperature	Ra	Beam Angle/ Lighting Spread	Average life	Certification
C35	E27/B22/ E14/B15d	5.5W	470 lm	3000K/4000K/6000K	≥80	160°	20000hrs	CE/Rhos/Erp
C35	E27/B22/ E14/B15d	5.5W	470 lm	3000K/4000K/6000K	≥80	160°	20000hrs	CE/Rhos/Erp

6. “PALUX” LED GX53 (main voltage)

Product Code	Watt	Lumen Output	Color Temperature	Ra	Average life	Certification
GX53	3W	200 lm	3000K/4000K/6000K	≥80	20000 hrs	LVD/EMC/Rohs
GX53	5W	360 lm	3000K/4000K/6000K	≥80	20000 hrs	LVD/EMC/Rohs
GX53	7W	620 lm	3000K/4000K/6000K	≥80	20000 hrs	LVD/EMC/Rohs
GX53	9W	760 lm	3000K/4000K/6000K	≥80	20000 hrs	LVD/EMC/Rohs

